

# ASTM F959 DuraSquirt®DTI Line Card

34120MGDSQ = 3/4 A325/120 Galvanized DuraSquirt®DTI

34   <b>BOLT DIAMETER</b> 34 = 3/4" 10 = 1" M20 = 20mm	120   <b>GRADE</b> 120 - A325/120 150 - A490/150 8 - 8.8 10 - 10.9	MG   <b>COATING*</b> MG - Galvanized PL - Plain WS - Weathering Steel Type 3 TDZ - Thermally Diffused Zinc Alloy * Additional coatings available on request.	DSQ   <b>INDICATOR</b> DSQ - DuraSquirt®
---	--	---	---

## Bolt Diameter

<b>A325</b>			<b>A490</b>		
		Pcs/Keg Wt			Pcs/Keg Wt
<b>1/2"</b>	123XXDSQ	1750/41 lb	<b>1/2"</b>	124XXDSQ	1750/40 lb
<b>5/8"</b>	583XXDSQ	1250/50 lb	<b>5/8"</b>	584XXDSQ	1250/48 lb
<b>3/4"</b>	343XXDSQ	1350/64 lb	<b>3/4"</b>	344XXDSQ	1000/64 lb
<b>7/8"</b>	783XXDSQ	850/65 lb	<b>7/8"</b>	784XXDSQ	700/58 lb
<b>1"</b>	103XXDSQ	600/66 lb	<b>1"</b>	104XXDSQ	600/64 lb
<b>1 1/8"</b>	1183XXDSQ	450/65 lb	<b>1 1/8"</b>	1184XXDSQ	450/64 lb
<b>1 1/4"</b>	1143XXDSQ	350/62 lb	<b>1 1/4"</b>	1144XXDSQ	350/60 lb
<b>1 3/8"</b>	1383XXDSQ	250/64 lb	<b>1 3/8"</b>	1384XXDSQ	250/62 lb
<b>1 1/2"</b>	1123XXDSQ	225/67 lb	<b>1 1/2"</b>	1124XXDSQ	200/59lb

## Bolt Diameter

<b>8.8</b>			<b>10.9</b>		
		Pcs/Keg Wt			Pcs/Keg Wt
<b>12</b>	M128XXDSQ	1750/42 lb	<b>12</b>	M1210XXDSQ	1750/40 lb
<b>16</b>	M168XXDSQ	1250/50 lb	<b>16</b>	M1610XXDSQ	1250/54 lb
<b>20</b>	M208XXDSQ	1000/64 lb	<b>20</b>	M2010XXDSQ	1000/62 lb
<b>22</b>	M228XXDSQ	900/62 lb	<b>22</b>	M2210XXDSQ	800/59 lb
<b>24</b>	M248XXDSQ	600/61 lb	<b>24</b>	M2410XXDSQ	600/59 lb
<b>27</b>	M278XXDSQ	500/64 lb	<b>27</b>	M2710XXDSQ	500/61 lb
<b>30</b>	M308XXDSQ	450/64 lb	<b>30</b>	M3010XXDSQ	350/58 lb
<b>36</b>	M368XXDSQ	250/62 lb	<b>36</b>	M3610XXDSQ	250/61 lb
			<b>42</b>	M4210XXDSQ	170/60 lb
			<b>48</b>	M4810XXDSQ	85/60 lb



the best way to bolt!™

1413 Rockingham Road  
Bellows Falls, VT 05101, USA

(800) 552-1999 & (802)-460-3100  
fax (802) 460-3104

appliedbolting.com

info@appliedbolting.com