

TRAINING • FIELD SUPPORT • TECHNICAL EXPERTISE



the best way to bolt!™

Bolting Completed in Three Easy Steps

1. Snug - Plies of steel in firm contact.
2. Squirt - Drive it till it squirts! No torque calibration or match-marking required.
3. Inspect - Visual indication of bolt tension; easy, safe and fast.



ASTM F959 **Squirter® DTIs** LINE CARD

with DuraSquirter® Formula

34120MGDSQ = 3/4 120 A325 Mechanically Galvanized Squirter® - DuraSquirter® DTI.

34	120	MG	DSQ
BOLT DIAMETER	GRADE	COATING*	INDICATOR
34 = 3/4"	120 = A325	MG = Mechanically Galvanized**	DSQ = DuraSquirter® Formula
10 = 1"	150 = A490	PL = Plain	
M20 = M20	8 = 8.8/120	WS = Weathering Steel/ Type 3	
	10 = 10.9/150	TDZ = Thermally Diffused Zinc	

Bolt Diameter

A325			A490		
		Pcs/Keg~			Pcs/Keg~
1/2"	12120XXDSQ	1750	1/2"	12150XXDSQ	1750
5/8"	58120XXDSQ	1250	5/8"	58150XXDSQ	1250
3/4"	34120XXDSQ	1350	3/4"	34150XXDSQ	1000
7/8"	78120XXDSQ	850	7/8"	78150XXDSQ	700
1"	10120XXDSQ	600	1"	10150XXDSQ	600
1 1/8"	118120XXDSQ	450	1 1/8"	118150XXDSQ	450
1 1/4"	114120XXDSQ	350	1 1/4"	114150XXDSQ	350
1 3/8"	138120XXDSQ	250	1 3/8"	138150XXDSQ	250
1 1/2"	112120XXDSQ	225	1 1/2"	112150XXDSQ	200

Bolt Diameter

8.8			10.9		
		Pcs/Keg~			Pcs/Keg~
M12	M128XXDSQ	1750	M12	M1210XXDSQ	1750
M16	M168XXDSQ	1250	M16	M1610XXDSQ	1250
M20	M208XXDSQ	1000	M20	M2010XXDSQ	1000
M22	M228XXDSQ	900	M22	M2210XXDSQ	800
M24	M248XXDSQ	600	M24	M2410XXDSQ	600
M27	M278XXDSQ	500	M27	M2710XXDSQ	500
M30	M308XXDSQ	450	M30	M3010XXDSQ	350
M36	M368XXDSQ	250	M36	M3610XXDSQ	250

* Other coatings available on request.
**Mechanically Galvanized coating is suitable for Hot Dipped Galv (HDG) fasteners



the best way to bolt!™
info@appliedbolting.com
appliedbolting.com

US: 1.800.552.1999 | Intl: 1.802.460.3100
1413 Rockingham Road Bellows Falls, Vermont, USA 05101